DS-K4T100
Pro Series Bolt Electric Lock



- Electric bolt, polished and brushed stainless steel, upport thrust of 800kg
- Working current: 900mA(Startup current), 100mA (standby), 12VDC + 10%
- Capable of 500,000 locking operations
- Suitable for wooden door, glass door, metal door and fireproof door
- Signal output of door lock status.

▪ Specification

General	
Power supply	12 VDC+10 %, 900 mA (startup current), 100 mA (standby)
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	0 to 95 % (relative humidity)
Dimensions	Lock Body: 205 mm × 35 mm × 40 mm (8.07" × 1.38" × 1.57") Armature Plate: 90 mm × 25 mm × 2 mm (3.54" × 0.98" × 0.07") Bolt: 16 mm × 16 mm (0.63" × 0.63")
Weight	0.7 kg (1.54 lb)
Material	Bolt: polished and brushed stainless steel
Thrust	Max. 800 kg (1764 lb)
Door type	Glass door, wooden door, metal door, fireproof door
Signal output	Signal output NC, COM contact of door status
Magnetic induction distance	8 mm (0.31")
Delay duration	0/3/6/9 s optional

▪ Available Model

DS-K4T100

DS-K4T100(USA-STD)

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®