

iBSG 3.5/Thebox

Basic configuration guide



N.V.K.INTER CO., LTD.



@nvkwireless



facebook.com/nvkinter



www.nvk.co.th

Topics

- Introduction
 - Product type
- Installation
 - Software VS. The box
 - License activation*
- Configure
 - Steps
 - Internet connectivity
 - Policy setup
 - Account creation
 - Device monitor
- Client access
 - Login, Logout
- Cloud service
 - Monitor, Events, Maintenance

Introduction

PRODUCT TYPE



N.V.K.INTER CO., LTD.

 @nvkwireless

 facebook.com/nvkinter

 www.nvk.co.th

Product type

- Software



- Appliance (The box)



Installation

SOFTWARE VS. THE BOX



N.V.K.INTER CO., LTD.


 @nvkwireless

 facebook.com/nvkinter


 www.nvk.co.th

Installation


- Software



- The box




Download



1. Download installation image at <https://ibsg.nvk.co.th/download/>
2. Burn ISO installation image to CD/DVD ROM

Install



1. Boot from installation CD
2. Press enter
3. Wait for installation to complete

Activate

Member Access

Login Register

 support@nvk.co.th



Add new license

First Generation License Note

License capacity will be changed to **Level 0 (150 User-Concurrent)**

Please input authorization code in this format: **ibsg_xxxxxx:password**

Please specify valid authorization code to proceed.

150b8f06dabb

Close Proceed

Activate license

Please specify both server name and request key to proceed software activation by 150b8f06dabb license.

Server name my new server

Request Key

1P433PUC42C705D30A05
D5E52583197158D8937EF
BEE44E94F657D0DB6E16
E0CC6BA9F3EC356131C9
EC600D3CD9B56DB650FC
CDAA2EE50C26BE43D6FF
61DEABD280E8F550CAF4
26DEADB4E4D64E11820
996EE9F003031

Close Proceed

Status Report Monitoring

About Contact

License Information

License ID	150b8f06dabb
Member	support
Company	N.V.K.INTER CO., LTD.
Server	my new server
Capacity	150 - (Base)
Issue	2015/02/01 7:13 pm
Expire	∞
Renewal	2015/02/16 7:13 pm (14 Day 23 Hr 59 Min 47 Sec)

Renew

Activation Information

1. Login to member portal at <https://ibsg.nvk.co.th/member>
2. Add license using PAK from NVK
3. Activate license



N.V.K.INTER CO., LTD.

 @nvkwireless

 facebook.com/nvkinter

 www.nvk.co.th

Configure STEPS



N.V.K.INTER CO., LTD.

 @nvkwireless

 facebook.com/nvkinter

 www.nvk.co.th

Configure steps

Internet connectivity



Policy setup



Account creation



Device monitor (optional)

Configure

INTERNET CONNECTIVITY



N.V.K.INTER CO., LTD.

 @nvkwireless

 facebook.com/nvkinter

 www.nvk.co.th

Management access



The screenshot shows a web interface for the 'Administration zone'. It features a login form with the following fields and controls:


- Loginname:** A text input field containing the value 'admin'.
- Password:** A text input field filled with ten black dots to mask the password.
- Duration:** A dropdown menu currently showing 'End of session'.
- Buttons:** Two buttons labeled 'Login' and 'Clear' are positioned below the input fields.

At the bottom of the form area, a red horizontal bar contains the copyright notice: '©2013 by N.V.K.INTER CO.,LTD v3.5-17beta'.


1. Access to <http://192.168.2.254/manage/>
2. Default credential is admin / admin123

Internet connectivity

- Single WAN



- Multi WAN



Internet connectivity (cont)

Network - Basic

The image displays three screenshots of a network configuration interface, specifically the 'WAN / Internet' section under the 'Network' tab. Each screenshot shows a different connection type selected in the 'Connection Type' dropdown menu.

- Left Screenshot (DHCP):** The 'Connection Type' is set to 'DHCP'. Fields for 'Static DNS', 'MTU' (1500), and 'MSS Clamp' (unchecked) are visible.
- Middle Screenshot (Static):** The 'Connection Type' is set to 'Static'. Fields include 'IP Address' (192.168.16.129), 'Subnet Mask' (255.255.255.0), 'Gateway' (192.168.16.254), 'Static DNS', 'MTU' (1500), and 'MSS Clamp' (unchecked).
- Right Screenshot (PPPoE):** The 'Connection Type' is set to 'PPPoE'. Fields include 'Username' (pppoe1), 'Password' (masked with dots), 'Authentication' (Auto), 'Service Name', 'Static DNS', 'MTU' (1492), 'MSS Clamp' (checked), 'Kernel Mode' (checked), and 'Alternate Link Check' (checked).

- **DHCP** – Automatically obtain an IP address from connected router*
- **Static** – Manually specify an IP address/subnet and gateway and DNS that provide by connected router or your ISP
- **PPPoE** – A widely use PPP over Ethernet protocol for broadband connection such as xDSL, FTTx to properly setup this connection type, your connected modem must operating in 'bridge' mode

Internet connectivity (cont)

Diagnostic - Ping

Diagnostic interface showing the Ping test results for www.google.com.

Navigation tabs: Status, Report, Manage, Monitoring, Network, Admin, System, Diagnostic.

Sub-tabs: ARP, DHCP, Ping, Trace.

Form fields:

- Address: www.google.com
- Interface: (Dropdown menu)
- Size (bytes): 32
- Count: 3
- Ping button

Ping result table:

#	Address	RX Bytes	TTL	RTT (ms)
1	61.19.2.29	40	55	2.44
2	61.19.2.29	40	55	2.15
3	61.19.2.29	40	55	2.22

You are logged in as 'admin' since 2015-03-14 08:52:03 am [171.99.103.243]

©2013 by N.V.K.INTER CO.,LTD

- ✓ Testing internet connection between iBSG and internet

Configure

POLICY SETUP



N.V.K.INTER CO., LTD.

 @nvkwireless

 facebook.com/nvkinter

 www.nvk.co.th

Policy setup

Manage - Policy



- Each policy will have its own properties that will be inherit by policy's members
- State – define state of policy's members
 - Active
 - Inactive
- Data rate – Maximum data rate for each policy's members
 - Download – 8 Kbps – 100Mbps or Unlimited
 - Upload – 8 Kbps – 100Mbps or Unlimited
- Transfer Quota – **Accumulated** data-transfer for each policy's members
- Usage Time – **Accumulated** usage time for each policy's members
- Valid Period – **Time period** after first time of usage for each policy's members
- Idle Timeout – Duration of inactivity before system automatically disconnect each policy's members

Policy setup (cont)

Manage - Policy

 Add / Edit

Id	0	
Name	30hr_in_3days	
State	☒ Active ☐ Inactive	
Identity	☐ Required ☒ None	
Type	☐ Postpaid ☒ Prepaid	
Price Rate	399	
Datarate DN/UP	1520	256 Kbps
Transfer Quota	0	Megabyte ▼
Daily Usage Time	0	Minute ▼
Weekly Usage Time	0	Minute ▼
Monthly Usage Time	0	Minute ▼
Usage Time	30	Hour ▼
Valid Period	3	Day ▼
Idle Timeout	0 (minutes)	
Comment		
Build Date	2013-06-16	
Build By	admin	
Add		

- Example - 1

- ☐ Policy name: 30hr_in_3days
- ☐ Data rate: 1.5Mbps / 256Kbps
- ☐ Usage time: 30 Hours
- ☐ Validity period 3 Days

- Each policy member will get maximum Download/Upload data rate **1.5 Mbps** and **256 Kbps** respectively

- Each policy member will have total **30 Hours** of usage time but only valid for **3 Days** after first time use

Policy setup (cont)

Manage - Policy

 Add / Edit

Id	0		
Name	nolimit_3days		
State	☒ Active ☐ Inactive		
Identity	☐ Required ☒ None		
Type	☐ Postpaid ☒ Prepaid		
Price Rate	299		
Datarate DN/UP	0	0	Kbps
Transfer Quota	0	Megabyte ▾	
Daily Usage Time	0	Minute ▾	
Weekly Usage Time	0	Minute ▾	
Monthly Usage Time	0	Minute ▾	
Usage Time	0	Hour ▾	
Valid Period	3	Day ▾	
Idle Timeout	0	(minutes)	
Comment			
Build Date	2013-06-16		
Build By	admin		
Add			

- Example - 2

- ☐ Policy name: nolimit_3days

- ☐ Data rate: Unlimited

- ☐ Valid Period 3Days

- Each policy member will get **maximum** Download/Upload data rate that available from your connection

- Each policy member will have total **3 Days usage** after first time use

Configure

ACCOUNT CREATION



N.V.K.INTER CO., LTD.

 @nvkwireless

 facebook.com/nvkinter

 www.nvk.co.th

Account creation

Manage - Account

The screenshot shows the 'Manage - Account' interface. The top navigation bar includes tabs for Status, Report, Manage (selected), Monitoring, Network, Admin, System, Diagnostic, Help, and Logout. The sub-navigation bar includes tabs for Policy, Account (selected), Identity, Portal, Passthrough, Walled Garden, Webfilter, and WSI. The main form area contains fields for Login, Policy (dropdown), Expire (Y/M/D), Build (Y/M/D), and Comment. There is a Search Type dropdown set to 'mixed' and buttons for Reset and Search. Below the form is a section titled 'Accounts' with a message 'No account defined.' and three numbered steps (1, 2, 3) with corresponding icons for adding, generating, and importing accounts. At the bottom left of the Accounts section are links for 'Add / Generate / Edit'.

- **Add** – create a single account at a time which suitable for small amount of account or specify user only
- **Generate** – generate large number of accounts up to 1,000 accounts at a time, suitable for hotel or apartment where these accounts can print out and sell at reception counter
- **Import** – import an account(s) from a CSV file suitable for some organization that would like to use existing user database

Account creation (cont)

Manage - Account

 **Add / Generate / Edit**

Id	0
Sold Now	☒ No ☐ Yes
State	☒ Active ☐ Inactive
Policy	30hr_in_3days ▼
Login	acc1
Password	1234 ☐ Hide
MAC	
Host	
Datarate DN/UP	0 0 Kbps ☐ Override
Maximum Login	1
Expire Date (Y M D)	2014 01 01 ☒ Not Expire
Comment	
Build Date	2013-06-16
Build By	admin
Add	

- Add example

- ☐ Policy: 30hr_in_3days

- ☐ Login: acc1

- ☐ Password: 1234

- An account named 'acc1' with password '1234' associated with '30hr_in_3days' policy will be created

Configure

DEVICE MONITOR



N.V.K.INTER CO., LTD.

 @nvkwireless

 facebook.com/nvkinter

 www.nvk.co.th

Device monitor

Monitoring - Device

#▲	Name	Group	IP Address	MAC Address	Model
1	EAP-600_1	default	10.0.1.241	∞	EAP-600
2	EAP-600_2	default	10.0.1.242	∞	EAP-600
3	EAP-600_3	default	10.0.1.243	∞	EAP-600
4	EAP-600_4	default	10.0.1.244	∞	EAP-600
7	EX2200_1	default	10.0.1.253	∞	Generic
8	EX2200_2	default	10.0.1.252	∞	Generic
10	DSLAM#3	dslam	10.0.1.3	∞	Generic
11	DSLAM#2	dslam	10.0.1.2	∞	Generic
12	DSLAM#1	dslam	10.0.1.1	∞	Generic
9/9					

- iBSG has build-in SNMP device monitoring feature, you can add any ip-enabled-device

Add / Edit

Id	1
Group	default
Name	EAP-600_1
IP Address	10.0.1.241
MAC Address	
Description	
SNMP	☒
Version	1
Vendor	EnGenius
Model	EAP-600
RO Community String	public
RW Community String	private
Traffic	☒
Interface	eth0 - 1 23 GB/1 06 GB [up]

Device monitor (cont)

Status - Device

Device Status

#▲	Name	Group	IP Address	15 m	10 m	5 m	Min RTT	Max RTT	SSID	Channel	Tx Power	↓Transferred	↑Transferred	Uptime	Client	Last seen	▼
1	EAP-600_1	default	10.0.1.241	●	●	●	0 ms	0 ms	NVK_Staff	Auto	20 dBm (100 mW)	1.19 GB	1.06 GB	77d 8h 31m 25s	6	2013/06/18 17:40:19	☒
2	EAP-600_2	default	10.0.1.242	●	●	●	0 ms	0 ms	NVK_Staff	Auto	20 dBm (100 mW)	3.46 GB	3.36 GB	5d 4h 16m 28s	1	2013/06/18 17:40:20	☐
3	EAP-600_3	default	10.0.1.243	●	●	●	0 ms	1 ms	NVK_Staff	Auto	20 dBm (100 mW)	546.00 MB	1.90 GB	77d 8h 31m 25s	3	2013/06/18 17:40:19	☐
4	EAP-600_4	default	10.0.1.244	●	●	●	0 ms	0 ms	NVK_Staff	Auto	20 dBm (100 mW)	1.78 GB	277.76 MB	21d 1h 5m 24s	7	2013/06/18 17:40:23	☐
7	EX2200_1	default	10.0.1.253	●	●	●	2 ms	3 ms	-	-	-	1.97 GB	3.64 GB	25d 2h 32m 43s	-	2013/06/18 17:40:24	☐
8	EX2200_2	default	10.0.1.252	●	●	●	3 ms	4 ms	-	-	-	3.22 GB	1.90 GB	25d 2h 33m 4s	-	2013/06/18 17:40:25	☐
10	DSLAM#3	dslam	10.0.1.3	●	●	●	-	-	-	-	-	-	-	-	-	-	☐
11	DSLAM#2	dslam	10.0.1.2	●	●	●	-	-	-	-	-	-	-	-	-	-	☐
12	DSLAM#1	dslam	10.0.1.1	●	●	●	-	-	-	-	-	-	-	-	-	-	☐
9												12.16 GB	12.12 GB		17		☐

- EnGenius Access Points (1) are exclusively compatible with iBSG, that means you can change its configuration such as Channel, Tx Power, SSID Name, SSID Security and Isolation through NetFi device configurator without entering each device web-interface after deployed

Device monitor

Status - Device

Device Configurator


Available

- EX2200_1 - (10.0.1.253)
- EX2200_2 - (10.0.1.252)
- DSLAM#3 - (10.0.1.3)
- DSLAM#2 - (10.0.1.2)
- DSLAM#1 - (10.0.1.1)

Selected

- EAP-600_1 - (10.0.1.241)
- EAP-600_2 - (10.0.1.242)
- EAP-600_3 - (10.0.1.243)
- EAP-600_4 - (10.0.1.244)

Ok Close



Maintenance

☐ Reboot

2.4Ghz Radio

☒ Channel/Frequency: Ch7-(2.442) ☒ Transmit Power: 22 dBm (158 mW)

5Ghz Radio

☐ Channel/Frequency: Auto ☐ Transmit Power:

2.4Ghz SSID

Enabled ☒ #1

Name: NVK_Staff

Hide (not broadcast): disabled

Authen/Encrypt: WPA2 PSK (AES)

Key/Passphrase:

Isolation (L2 isolation): enabled

VID: 1



Device Configurator

Name	IP Address	Status	Result
EAP-600_1	10.0.1.241	processing...	
EAP-600_2	10.0.1.242	success	
EAP-600_3	10.0.1.243	processing...	
EAP-600_4	10.0.1.244	processing...	

Exit

Client access

LOGIN, LOGOUT



N.V.K.INTER CO., LTD.

 @nvkwireless

 facebook.com/nvkinter

 www.nvk.co.th

Client access

- Login

iBSG3.5

DEVICE MONITOR
Hot-Spot Gateway
Log Recorder
AP Controller

Please login


Loginname:

Password:

☐ Remember Me

Announcement

Announcement message here



Login successfully

Welcome to Hi-Speed internet, You can type 'logout.' in address bar and hit enter to logout.

Policy/Package: nolimit_3days

Time remain: ∞

Time quota: ∞

Transfer remain: ∞

Transfer quota: ∞

Valid/Expire date: 2013/06/21 13:58:30

© 2013 NETFINETWORK



Google

Google Search

I'm Feeling Lucky

Client access

- Logout



Cloud service




N.V.K.INTER CO., LTD.

 @nvkwireless

 facebook.com/nvkinter

 www.nvk.co.th

Monitor



Events

 **ibsg**
Net in Control

max@nvk.co.th

[Overview](#)
[Events 4](#)
[Servers](#)
[Licenses](#)
[Profile](#)

Events

Show entries

Search:

#	Time	Server	Source	Event	Severity	Status
1	14/03/2015 - 03:31:18	Devel@Office	REMOTE	Server started	INFO	 
4	13/03/2015 - 11:45:27	Devel@Home	REMOTE	Server started	INFO	 
3	13/03/2015 - 11:44:31	Devel@Home	REMOTE	Server halt	INFO	 
2	13/03/2015 - 11:41:21	Devel@Home	REMOTE	Server started	INFO	 
4						

[Previous](#) [1](#) [Next](#)

[Acknowledge All](#) [Remove All](#)

Maintenance

nvk iBSG
Net in Control

max@

[Overview](#)
[Events 4](#)
[Servers](#)
[Licenses](#)
[Profile](#)

Servers

Show entries

Search:

#	Name	Uptime	IP Address	Version	Clients/Capacity	Last Seen	
8	Sirisin35	6d 4h 26m 51s	110.171.170.208	3.5-17beta	45/200	3m 19s	
7	U-Place	6d 4h 28m 15s	183.89.147.151	3.5-17beta	100/200	1m 37s	
6	Devel@VMx	1h 26m 39s	180.183.117.184	3.5-17beta	0/500	5d	U-Place Reboot Reset Admin
5	2014-0269 (Pacific A)	9d 19h 48m 39s	61.90.175.2	3.5-17beta	0/150	34s	
4	2014-0161 (The Kump I)	3d 15h 21m 57s	61.91.41.62	3.5-17beta	3/150	28s	
3	2013-0075 (The Kump G)	10d 1h 6m	61.91.37.154	3.5-17beta	0/1000	3m 40s	
2	Devel@Home	1d 10m 59s	49.49.251.36	3.5-17beta	0/150	4m 51s	
1	Devel@Office	8h 25m 39s	110.78.162.42	3.5-17beta	0/150	4m 29s	
8					148		

Previous 1