HF-KS3
Interlinked Smoke Alarm Kit



- HF-LINK Interconnection.
- 433 smoke alarm kit contains HF-PR1-R 1pcs and HF-S3E-R 3pcs .
- 868 smoke alarm kit contains HF-PR1-R8 1pcs and HF-S3E-R8 3pcs .

▪ Specification

General	
Using Environment	HF-KS3:0 °C to 55 °C；≤95% relative humidity (RH) 0 °C to 55 °C；≤95% relative humidity (RH)
Communication Mode	HF-KS3:HF-Link HF-KS3-R8(O-STD):HF-Link/868 HF-KS3-R(O-STD):HF-Link/433
Mounting Scenario	Indoor
Weight	350.5 g
Dimension (L × W × H)	HF-KS3:L 265 mm * W 170 mm * H 120 mm (for package) L 260 mm * W 250 mm * H 70 mm (for package)
Complete Set	HF-KS3-R8(O-STD):HF-PR1-R8 *1 and HF-S3E-R8 *3 HF-KS3-R(O-STD):HF-PR1-R *1 and HF-S3E-R *3

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®